


**GenX3™ 1200V
IGBT w/ Diode**
IXGN82N120C3H1


$$V_{CES} = 1200V$$

$$I_{C110} = 58A$$

$$V_{CE(sat)} \leq 3.9V$$

 High-Speed PT IGBT for
20-50 kHz Switching


| Symbol | Test Conditions | Maximum Ratings | |
|----------------|---|-----------------------|------------|
| V_{CES} | $T_J = 25^\circ C$ to $150^\circ C$ | 1200 | V |
| V_{CGR} | $T_J = 25^\circ C$ to $150^\circ C$, $R_{GE} = 1M\Omega$ | 1200 | V |
| V_{GES} | Continuous | ± 20 | V |
| V_{GEM} | Transient | ± 30 | V |
| I_{C25} | $T_C = 25^\circ C$ | 130 | A |
| I_{C110} | $T_C = 110^\circ C$ | 58 | A |
| I_{F110} | $T_C = 110^\circ C$ | 42 | A |
| I_{CM} | $T_C = 25^\circ C$, 1ms | 500 | A |
| SSOA | $V_{GE} = 15V$, $T_{VJ} = 125^\circ C$, $R_G = 3\Omega$ | $I_{CM} = 164$ | A |
| (RBSOA) | Clamped Inductive Load | $V_{CE} \leq V_{CES}$ | |
| P_C | $T_C = 25^\circ C$ | 595 | W |
| T_J | | -55 ... +150 | $^\circ C$ |
| T_{JM} | | 150 | $^\circ C$ |
| T_{stg} | | -55 ... +150 | $^\circ C$ |
| V_{ISOL} | 50/60Hz | $t = 1min$ | 2500 V~ |
| | $I_{ISOL} \leq 1mA$ | $t = 1s$ | 3000 V~ |
| M_d | Mounting Torque | 1.5/13 | Nm/lb.in. |
| | Terminal Connection Torque | 1.3/11.5 | Nm/lb.in. |
| Weight | | 30 | g |

 SOT-227B, miniBLOC
 E153432

 G = Gate, C = Collector, E = Emitter
 ① either emitter terminal can be used as
Main or Kelvin Emitter

Features

- Optimized for Low Switching Losses
- Square RBSOA
- High Current Capability
- Isolation Voltage 2500 V~
- Anti-Parallel Ultra Fast Diode
- International Standard Package

Advantages

- High Power Density
- Low Gate Drive Requirement


Applications

- Power Inverters
- UPS
- SMPS
- PFC Circuits
- Welding Machines
- Lamp Ballasts

| Symbol | Test Conditions ($T_J = 25^\circ C$, Unless Otherwise Specified) | Characteristic Values | | |
|---------------|---|-----------------------|------|--------------------|
| | | Min. | Typ. | Max. |
| $V_{GE(th)}$ | $I_C = 1mA$, $V_{CE} = V_{GE}$ | 3.0 | | 5.0 V |
| I_{CES} | $V_{CE} = V_{CES}$, $V_{GE} = 0V$, Note 1 $T_J = 125^\circ C$ | | | 50 μA 6 mA |
| I_{GES} | $V_{CE} = 0V$, $V_{GE} = \pm 20V$ | | | ± 200 nA |
| $V_{CE(sat)}$ | $I_C = 82A$, $V_{GE} = 15V$, Note 2 | | 3.3 | 3.9 V |

| Symbol | Test Conditions ($T_J = 25^\circ\text{C}$, Unless Otherwise Specified) | Characteristic Values | | |
|--------------|---|-----------------------|------|-------------------------|
| | | Min. | Typ. | Max. |
| g_{fs} | $I_C = 60\text{A}$, $V_{CE} = 10\text{V}$, Note 2 | 38 | 62 | S |
| C_{ies} | $V_{CE} = 25\text{V}$, $V_{GE} = 0\text{V}$, $f = 1\text{MHz}$ | | 7900 | pF |
| C_{oes} | | | 685 | pF |
| C_{res} | | | 197 | pF |
| $Q_{g(on)}$ | $I_C = 82\text{A}$, $V_{GE} = 15\text{V}$, $V_{CE} = 0.5 \cdot V_{CES}$ | | 340 | nC |
| Q_{ge} | | | 55 | nC |
| Q_{gc} | | | 145 | nC |
| $t_{d(on)}$ | Inductive load, $T_J = 25^\circ\text{C}$ | | 30 | ns |
| t_{ri} | | | 77 | ns |
| E_{on} | $I_C = 82\text{A}$, $V_{GE} = 15\text{V}$ | | 5.0 | mJ |
| $t_{d(off)}$ | $V_{CE} = 0.5 \cdot V_{CES}$, $R_G = 2\Omega$ | | 194 | ns |
| t_{fi} | Note 3 | | 100 | ns |
| E_{off} | | | 2.5 | 5.0 mJ |
| $t_{d(on)}$ | Inductive load, $T_J = 125^\circ\text{C}$ | | 32 | ns |
| t_{ri} | | | 80 | ns |
| E_{on} | $I_C = 82\text{A}$, $V_{GE} = 15\text{V}$ | | 6.8 | mJ |
| $t_{d(off)}$ | $V_{CE} = 0.5 \cdot V_{CES}$, $R_G = 2\Omega$ | | 230 | ns |
| t_{fi} | Note 3 | | 270 | ns |
| E_{off} | | | 4.0 | mJ |
| R_{thJC} | | | | 0.21 $^\circ\text{C/W}$ |
| R_{thCK} | | 0.05 | | $^\circ\text{C/W}$ |

SOT-227B miniBLOC (IXGN)



| SYM | INCHES | | MILLIMETERS | |
|-----|--------|-------|-------------|-------|
| | MIN | MAX | MIN | MAX |
| A | 1.240 | 1.255 | 31.50 | 31.88 |
| B | .307 | .323 | 7.80 | 8.20 |
| C | .161 | .169 | 4.09 | 4.29 |
| D | .161 | .169 | 4.09 | 4.29 |
| E | .161 | .169 | 4.09 | 4.29 |
| F | .587 | .595 | 14.91 | 15.11 |
| G | 1.186 | 1.193 | 30.12 | 30.30 |
| H | 1.496 | 1.505 | 38.00 | 38.23 |
| J | .460 | .481 | 11.68 | 12.22 |
| K | .351 | .378 | 8.92 | 9.60 |
| L | .030 | .033 | 0.76 | 0.84 |
| M | .496 | .506 | 12.60 | 12.85 |
| N | .990 | 1.001 | 25.15 | 25.42 |
| O | .078 | .084 | 1.98 | 2.13 |
| P | .195 | .235 | 4.95 | 5.97 |
| Q | 1.045 | 1.059 | 26.54 | 26.90 |
| R | .155 | .174 | 3.94 | 4.42 |
| S | .186 | .191 | 4.72 | 4.85 |
| T | .968 | .987 | 24.59 | 25.07 |
| U | -.002 | .004 | -0.05 | 0.1 |

Reverse Diode (FRED)

| Symbol | Test Conditions ($T_J = 25^\circ\text{C}$, Unless Otherwise Specified) | Characteristic Values | | |
|------------|---|-----------------------|------|-------------------------|
| | | Min. | Typ. | Max. |
| V_F | $I_F = 60\text{A}$, $V_{GE} = 0\text{V}$, Note 1 | | | 2.5 V |
| | $T_J = 150^\circ\text{C}$ | | 1.4 | 1.8 V |
| I_{RM} | $I_F = 60\text{A}$, $V_{GE} = 0\text{V}$, $-di_F/dt = 200\text{A}/\mu\text{s}$, $V_R = 300\text{V}$ | | 8.3 | A |
| t_{rr} | | | 140 | ns |
| R_{thJC} | | | | 0.42 $^\circ\text{C/W}$ |

Notes:

1. Part must be heatsunk for high-temp I_{ces} measurement.
2. Pulse test, $t \leq 300\mu\text{s}$, duty cycle, $d \leq 2\%$.
3. Switching times & energy losses may increase for higher $V_{CE}(\text{Clamp})$, T_J or R_G .

ADVANCE TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from a subjective evaluation of the design, based upon prior knowledge and experience, and constitute a "considered reflection" of the anticipated result. IXYS reserves the right to change limits, test conditions, and dimensions without notice.

IXYS Reserves the Right to Change Limits, Test Conditions, and Dimensions.

| | | | | | | | | | | |
|--|-----------|-----------|-----------|-----------|--------------|--------------|--------------|--------------|--------------|-------------|
| IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: | 4,835,592 | 4,931,844 | 5,049,961 | 5,237,481 | 6,162,665 | 6,404,065 B1 | 6,683,344 | 6,727,585 | 7,005,734 B2 | 7,157,338B2 |
| | 4,850,072 | 5,017,508 | 5,063,307 | 5,381,025 | 6,259,123 B1 | 6,534,343 | 6,710,405 B2 | 6,759,692 | 7,063,975 B2 | |
| | 4,881,106 | 5,034,796 | 5,187,117 | 5,486,715 | 6,306,728 B1 | 6,583,505 | 6,710,463 | 6,771,478 B2 | 7,071,537 | |



Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.