

OptiMOS™3 Power-Transistor

Features

- N-channel, normal level
- Excellent gate charge $\times R_{DS(on)}$ product (FOM)
- Very low on-resistance $R_{DS(on)}$
- 175 °C operating temperature
- Pb-free lead plating; RoHS compliant
- Qualified according to JEDEC¹⁾ for target application
- Ideal for high-frequency switching and synchronous rectification
- Halogen-free according to IEC61249-2-21


Product Summary

V_{DS}	120	V
$R_{DS(on),max}$	4.8	mΩ
I_D	100	A




Halogen-Free

PG-T0220-3



Type	Package	Marking
IPP048N12N3 G	PG-T0220-3	048N12N



Maximum ratings, at $T_j=25$ °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	$T_C=25$ °C ²⁾	100	A
		$T_C=100$ °C	100	
Pulsed drain current ³⁾	$I_{D,pulse}$	$T_C=25$ °C	400	
Avalanche energy, single pulse	E_{AS}	$I_D=100$ A, $R_{GS}=25$ Ω	740	mJ
Reverse diode dv/dt	dv/dt	$I_D=100$ A, $V_{DS}=80$ V, $di/dt=100$ A/μs, $T_{j,max}=175$ °C	6	kV/μs
Gate source voltage ⁴⁾	V_{GS}		±20	V
Power dissipation	P_{tot}	$T_C=25$ °C	300	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 175	°C
IEC climatic category; DIN IEC 68-1			55/175/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Thermal characteristics

Thermal resistance, junction - case	R_{thJC}		-	-	0.5	K/W
Thermal resistance, junction - ambient	R_{thJA}	minimal footprint	-	-	62	
		6 cm ² cooling area ⁵⁾	-	-	40	

Electrical characteristics, at $T_j=25$ °C, unless otherwise specified

Static characteristics

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0$ V, $I_D=1$ mA	120	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$, $I_D=230$ µA	2	3	4	
Zero gate voltage drain current	I_{DSS}	$V_{DS}=120$ V, $V_{GS}=0$ V, $T_j=25$ °C	-	0.1	1	µA
		$V_{DS}=120$ V, $V_{GS}=0$ V, $T_j=125$ °C	-	10	100	
Gate-source leakage current	I_{GSS}	$V_{GS}=20$ V, $V_{DS}=0$ V	-	1	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	$V_{GS}=10$ V, $I_D=100$ A	-	4.1	4.8	mΩ
Gate resistance	R_G		-	1.8	-	Ω
Transconductance	g_{fs}	$ V_{DS} >2 I_D R_{DS(on)max}$, $I_D=100$ A	81	162	-	s

¹⁾J-STD20 and JESD22

²⁾ Current is limited by bondwire; with an $R_{thJC}=0.5$ K/W the chip is able to carry 161 A.

³⁾ See figure 3

⁴⁾ $T_{jmax}=150$ °C and duty cycle D=0.01 for $V_{gs}<-5$ V

⁵⁾ Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm² (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

Dynamic characteristics

Input capacitance	C_{iss}	$V_{GS}=0 \text{ V}, V_{DS}=60 \text{ V}, f=1 \text{ MHz}$	-	9030	12000	pF
Output capacitance	C_{oss}		-	1150	1530	
Reverse transfer capacitance	C_{rss}		-	54	81	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=60 \text{ V}, V_{GS}=10 \text{ V}, I_D=50 \text{ A}, R_G=1.6 \Omega$	-	31	-	ns
Rise time	t_r		-	55	-	
Turn-off delay time	$t_{d(off)}$		-	64	-	
Fall time	t_f		-	19	-	

Gate Charge Characteristics⁶⁾

Gate to source charge	Q_{gs}	$V_{DD}=60 \text{ V}, I_D=100 \text{ A}, V_{GS}=0 \text{ to } 10 \text{ V}$	-	46	-	nC
Gate to drain charge	Q_{gd}		-	33	-	
Switching charge	Q_{sw}		-	52	-	
Gate charge total	Q_g		-	137	182	
Gate plateau voltage	$V_{plateau}$		-	5.1	-	V
Output charge	Q_{oss}	$V_{DD}=60 \text{ V}, V_{GS}=0 \text{ V}$	-	158	210	nC


Reverse Diode

Diode continuous forward current	I_s	$T_C=25 \text{ }^\circ\text{C}$	-	-	100	A
Diode pulse current	$I_{s,pulse}$		-	-	400	
Diode forward voltage	V_{SD}	$V_{GS}=0 \text{ V}, I_F=100 \text{ A}, T_j=25 \text{ }^\circ\text{C}$	-	1.0	1.2	V
Reverse recovery time	t_{rr}	$V_R=60 \text{ V}, I_F=I_s, di_F/dt=100 \text{ A}/\mu\text{s}$	-	113	-	ns
Reverse recovery charge	Q_{rr}		-	315	-	


⁶⁾ See figure 16 for gate charge parameter definition

1 Power dissipation

$$P_{\text{tot}} = f(T_c)$$



2 Drain current

$$I_D = f(T_c); V_{GS} \geq 10 \text{ V}$$


3 Safe operating area


$$I_D = f(V_{DS}); T_c = 25 \text{ °C}; D = 0$$

parameter: t_p



4 Max. transient thermal impedance


$$Z_{\text{thJC}} = f(t_p)$$



parameter: $D = t_p/T$






5 Typ. output characteristics
 $I_D = f(V_{DS})$; $T_j = 25 \text{ }^\circ\text{C}$


parameter: V_{GS}

6 Typ. drain-source on resistance
 $R_{DS(on)} = f(I_D)$; $T_j = 25 \text{ }^\circ\text{C}$

parameter: V_{GS}

7 Typ. transfer characteristics
 $I_D = f(V_{GS})$; $|V_{DS}| > 2|I_D|R_{DS(on)max}$


parameter: T_j

8 Typ. forward transconductance
 $g_{fs} = f(I_D)$; $T_j = 25 \text{ }^\circ\text{C}$





9 Drain-source on-state resistance
 $R_{DS(on)} = f(T_j); I_D = 100 \text{ A}; V_{GS} = 10 \text{ V}$

10 Typ. gate threshold voltage
 $V_{GS(th)} = f(T_j); V_{GS} = V_{DS}$


 parameter: I_D

11 Typ. capacitances
 $C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$

12 Forward characteristics of reverse diode
 $I_F = f(V_{SD})$

 parameter: T_j


13 Avalanche characteristics
 $I_{AS} = f(t_{AV})$; $R_{GS} = 25 \Omega$

parameter: $T_{j(\text{start})}$

14 Typ. gate charge
 $V_{GS} = f(Q_{\text{gate}})$; $I_D = 100 \text{ A pulsed}$

parameter: V_{DD}

15 Drain-source breakdown voltage
 $V_{BR(DSS)} = f(T_j)$; $I_D = 1 \text{ mA}$

16 Gate charge waveforms


PG-T0220-3: Outline


DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.57	0.169	0.180
A1	1.17	1.40	0.046	0.055
A2	2.15	2.72	0.085	0.107
b	0.65	0.86	0.026	0.034
b1	0.95	1.40	0.037	0.055
b2	0.95	1.15	0.037	0.045
b3	0.65	1.15	0.026	0.045
c	0.33	0.60	0.013	0.024
D	14.81	15.95	0.583	0.628
D1	8.51	9.45	0.335	0.372
D2	12.19	13.10	0.480	0.516
E	9.70	10.36	0.382	0.408
E1	6.50	8.60	0.256	0.339
e	2.54		0.100	
e1	5.08		0.200	
N	3		3	
H1	5.90	6.90	0.232	0.272
L	13.00	14.00	0.512	0.551
L1	-	4.80	-	0.189
øP	3.60	3.89	0.142	0.153
Q	2.60	3.00	0.102	0.118

DOCUMENT NO.
Z8B00003318
SCALE
0
2.5
0
2.5
5mm
EUROPEAN PROJECTION
ISSUE DATE
23-08-2007
REVISION
05

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2010 Infineon Technologies AG

All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.