



**Trench™  
Power MOSFET**
**IXTA160N10T  
IXTP160N10T**
**N-Channel Enhancement Mode  
Avalanche Rated**

 **$V_{DSS}$  = 100V  
 $I_{D25}$  = 160A  
 $R_{DS(on)}$  ≤ 7.0mΩ**
**TO-263  
(IXTA)**

**TO-220  
(IXTP)**

**G = Gate      D = Drain  
S = Source      Tab = Drain**

Symbol	Test Conditions	Maximum Ratings		
$V_{DSS}$	$T_J = 25^\circ\text{C}$ to $175^\circ\text{C}$	100		V
$V_{DGR}$	$T_J = 25^\circ\text{C}$ to $175^\circ\text{C}$ , $R_{GS} = 1\text{M}\Omega$	100		V
$V_{GSS}$	Continuous	± 20		V
$V_{GSM}$	Transient	± 30		V
$I_{D25}$	$T_c = 25^\circ\text{C}$ (Chip Capability)	160		A
$I_{L(\text{RMS})}$	Lead Current Limit, RMS	120		A
$I_{DM}$	$T_c = 25^\circ\text{C}$ , Pulse Width Limited by $T_{JM}$	430		A
$I_A$	$T_c = 25^\circ\text{C}$	25		A
$E_{AS}$	$T_c = 25^\circ\text{C}$	500		mJ
$dV/dt$	$I_s \leq I_{DM}$ , $V_{DD} \leq V_{DSS}$ , $T_J \leq 175^\circ\text{C}$	3		V/ns
$P_D$	$T_c = 25^\circ\text{C}$	430		W
$T_J$		-55 ... +175		°C
$T_{JM}$		175		°C
$T_{stg}$		-55 ... +175		°C
$T_L$	Maximum Lead Temperature for Soldering	300		°C
$T_{SOLD}$	1.6 mm (0.062in.) from Case for 10s	260		°C
$F_c$	Mounting Force (TO-263)	10..65 / 2.2..14.6		N/lb
$M_d$	Mounting Torque (TO-220)	1.13 / 10		Nm/lb.in
<b>Weight</b>	TO-263	2.5		g
	TO-220	3.0		g

Symbol	Test Conditions ( $T_J = 25^\circ\text{C}$ Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
$BV_{DSS}$	$V_{GS} = 0\text{V}$ , $I_D = 250\mu\text{A}$	100		V
$V_{GS(\text{th})}$	$V_{DS} = V_{GS}$ , $I_D = 250\mu\text{A}$	2.5		4.5 V
$I_{GSS}$	$V_{GS} = \pm 20\text{V}$ , $V_{DS} = 0\text{V}$		±200	nA
$I_{DSS}$	$V_{DS} = V_{DSS}$ , $V_{GS} = 0\text{V}$ $T_J = 150^\circ\text{C}$		5	μA
$R_{DS(on)}$	$V_{GS} = 10\text{V}$ , $I_D = 25\text{A}$ , Notes 1& 2	6.1	7.0	mΩ

**Features**

- Ultra-Low On Resistance
- Avalanche Rated
- Low Package Inductance
  - Easy to Drive and to Protect
- 175°C Operating Temperature
- Fast Intrinsic Diode

**Advantages**

- Easy to Mount
- Space Savings
- High Power Density

**Applications**


- Automotive
  - Motor Drives
  - 42V Power Bus
  - ABS Systems
- DC/DC Converters and Off-line UPS
- Primary Switch for 24V and 48V Systems
- Distributed Power Architectures and VRMs
- Electronic Valve Train Systems
- High Current Switching Applications
- High Voltage Synchronous Rectifier

Symbol	Test Conditions ( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
$g_{fs}$	$V_{DS} = 10\text{V}$ , $I_D = 60\text{A}$ , Note 1	65	102	S
$C_{iss}$ $C_{oss}$ $C_{rss}$	$V_{GS} = 0\text{V}$ , $V_{DS} = 25\text{V}$ , $f = 1\text{MHz}$	6600		pF
		880		pF
		135		pF
$t_{d(on)}$ $t_r$ $t_{d(off)}$ $t_f$	<b>Resistive Switching Times</b> $V_{GS} = 10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 25\text{A}$ $R_G = 5\Omega$ (External)	33		ns
		61		ns
		49		ns
		42		ns
$Q_{g(on)}$ $Q_{gs}$ $Q_{gd}$	$V_{GS} = 10\text{V}$ , $V_{DS} = 0.5 \cdot V_{DSS}$ , $I_D = 25\text{A}$	132		nC
		37		nC
		40		nC
$R_{thJC}$			0.35	$^\circ\text{C}/\text{W}$
$R_{thCH}$	TO-220	0.50		$^\circ\text{C}/\text{W}$


### Source-Drain Diode

Symbol	Test Conditions ( $T_J = 25^\circ\text{C}$ , Unless Otherwise Specified)	Characteristic Values		
		Min.	Typ.	Max.
$I_s$	$V_{GS} = 0\text{V}$		160	A
$I_{SM}$	Repetitive, Pulse Width Limited by $T_{JM}$		430	A
$V_{SD}$	$I_F = 25\text{A}$ , $V_{GS} = 0\text{V}$ , Note 1		1.0	V
$t_{rr}$	$I_F = 25\text{A}$ , $V_{GS} = 0\text{V}$ -di/dt = $100\text{A}/\mu\text{s}$ , $V_R = 50\text{V}$	60		ns

Notes: 1. Pulse test,  $t \leq 300\mu\text{s}$ ; duty cycle,  $d \leq 2\%$ .  
 2. On through-hole packages,  $R_{DS(on)}$  Kelvin test contact location must be 5mm or less from the package body.

**TO-263 Outline**


SYM	INCHES		MILLIMETER	
	MIN	MAX	MIN	MAX
A	.170	.185	4.30	4.70
A1	.000	.008	0.00	0.20
A2	.091	.098	2.30	2.50
b	.028	.035	0.70	0.90
b2	.046	.060	1.18	1.52
C	.018	.024	0.45	0.60
C2	.049	.060	1.25	1.52
D	.340	.370	8.63	9.40
D1	.300	.327	7.62	8.30
E	.380	.410	9.65	10.41
E1	.270	.330	6.86	8.38
e	.100	BSC	2.54	BSC
H	.580	.620	14.73	15.75
L	.075	.105	1.91	2.67
L1	.039	.060	1.00	1.52
L2	—	.070	—	1.77
L3	.010	BSC	0.254	BSC

**TO-220 Outline**








SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.169	.185	4.30	4.70
A1	.047	.055	1.20	1.40
A2	.079	.106	2.00	2.70
b	.024	.039	0.60	1.00
b2	.045	.057	1.15	1.45
c	.014	.026	0.35	0.65
D	.587	.626	14.90	15.90
D1	.335	.370	8.50	9.40
(D2)	.500	.531	12.70	13.50
E	.382	.406	9.70	10.30
(E1)	.283	.323	7.20	8.20
e	.100	BSC	2.54	BSC
e1	.200	BSC	5.08	BSC
H1	.244	.268	6.20	6.80
L	.492	.547	12.50	13.90
L1	.110	.154	2.80	3.90
ØP	.134	.150	3.40	3.80
Q	.106	.126	2.70	3.20







### PRELIMINARY TECHNICAL INFORMATION

The product presented herein is under development. The Technical Specifications offered are derived from data gathered during objective characterizations of preliminary engineering lots; but also may yet contain some information supplied during a pre-production design evaluation. IXYS reserves the right to change limits, test conditions, and dimensions without notice.


IXYS reserves the right to change limits, test conditions, and dimensions.

IXYS MOSFETs and IGBTs are covered by one or more of the following U.S. patents: 4,835,592 4,931,844 5,049,961 5,237,481 6,162,665 6,404,065 B1 6,683,344 6,727,585 7,005,734 B2 7,157,338B2 4,860,072 5,017,508 5,063,307 5,381,025 6,259,123 B1 6,534,343 6,710,405 B2 6,759,692 7,063,975 B2 4,881,106 5,034,796 5,187,117 5,486,715 6,306,728 B1 6,583,505 6,710,463 6,771,478 B2 7,071,537


**Fig. 1. Output Characteristics @  $T_J = 25^\circ\text{C}$** 

**Fig. 2. Extended Output Characteristics @  $T_J = 25^\circ\text{C}$** 

**Fig. 3. Output Characteristics @  $T_J = 150^\circ\text{C}$** 

**Fig. 4.  $R_{DS(on)}$  Normalized to  $I_D = 160\text{A}$  Value vs. Junction Temperature**

**Fig. 5.  $R_{DS(on)}$  Normalized to  $I_D = 80\text{A}$  Value vs. Drain Current**

**Fig. 6. Drain Current vs. Case Temperature**


**Fig. 7. Input Admittance**

**Fig. 8. Transconductance**

**Fig. 9. Forward Voltage Drop of Intrinsic Diode**

**Fig. 10. Gate Charge**

**Fig. 11. Capacitance**

**Fig. 12. Maximum Transient Thermal Impedance**



**Fig. 13. Resistive Turn-on**  
 Rise Time vs. Junction Temperature




**Fig. 14. Resistive Turn-on**  
 Rise Time vs. Drain Current




**Fig. 15. Resistive Turn-on**  
 Switching Times vs. Gate Resistance




**Fig. 16. Resistive Turn-off**  
 Switching Times vs. Junction Temperature



**Fig. 17. Resistive Turn-off**  
 Switching Times vs. Drain Current



**Fig. 18. Resistive Turn-off**  
 Switching Times vs. Gate Resistance





---

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).